


Product Specifications for F20515-18PC

•	Todact opecinications for E20010-101 C		
	Job Name:	Job Type:	
		31	
	Quantity:	Comments	



E20515-18PC Larmes 9-Light LED Pendant



Finish Polished Chrome

Lam	pı.	ng	7
Num	be	er	0

of Bulb(s) **Light Type** LED **Bulb Type** G4 LED Max Bulb Wattage 1.5 **Max Fixture Wattage** 13.5 Rated Life ±30,000 Hours ±864 **Rated Lumens** Color Temp ±3,000 K Bulb(s) Included Yes Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer Yes Standard/Lutron® **Dimmable** CL or Leviton® LED

Glass/Shade

Clear

Measurements

Width 22.75" Height 16.50" Length 22.75" Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A **HCO** N/A Min Overall Height 16.50" Max Overall Height 140.50" Hanging Weight 18.74 lb(s) **Height Adjustable** N/A Slope N/A Chain Length N/A Wire Length N/A N/A **Canopy Width** N/A Canopy Height **Canopy Length** N/A

Product Category

Single Pendant

Shipping Carton Weight 25.77 lb(s) Carton Width 26.50" **Carton Height** 11.00" **Carton Length** 28.50" **Carton Cubic Feet** N/A **Master Pack Master Pack Weight** N/A Master Pack Width N/A **Master Pack Height** N/A **Master Pack Length** N/A **Master Cubic Feet** N/A **UPS Shippable**

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

UPC Code	845094060956
Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.