

5 5/8" Color Preference Down Light

11 Watts 670lms LED 53186143

SPECIFICATIONS



The ETi LED 11 Watts, 670 lumen 5 5/8" Recessed Can Retrofit Kit while reducing energy and maintenance cost when compared with conventional light sources, Fits standard 5 5/8" recessed can with spring or friction clips and is IC rated for direct installation. no lead or mercury. Warranty 5 years. Suitable for installations from 4° F to 95°F.

These new state-of-the-art LED recessed Color Preference downlights are available in settable white LED color temperatures: Warm White 3000K, Natural White 4000K and Pure White 5000K.

ETi SSL offers an expansive line of energy efficient LED recessed can kits. These kits are approved for most wiring and ceiling types. Typical applications include; indoor recessed can, high hat in residential, office, retail, restaurant, school, hospital and hotel/motel locations.

KEY FEATURES & BENEFITS

- 11 Watts
- Single-volt 120V
- 670 lumen, 3000K/4000K/5000K Color Preference
- Dimmable
- UL damp location rated
- No UV, IR or mercury
- Warranty for 5 years

FIXTURE DIMENSIONS



SKU# 53186143
Dimension A 3.15"
Dimension B 7.48"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etissl.com/fcc15b

5"/6" Color Preference Down Light

11 Watts 670lm_s LED 53186143

SPECIFICATION DATA

Item Number	Description	Watts	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	DUV	CBCP	Beam Angle	Operating Frequency
53186143	5"/6" Color Preference Down Light	11	120	50,000 hours	670	3000/ 4000/ 5000	90	>0.94	14	/	/	120	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens													
³ in compliance with ANSI C77.378 201X													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs) Dimensions (H x L x W)	Master Pack QTY	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
53186143	84948900 6345	7.48" x 7.48" x 3.15"	0.81	N/A	N/A	N/A	N/A	4	508494890 06340	15.66" x 9.92" x 9.345"	6.4

ETI

LED **lighting facts**[®]
A Program of the U.S. DOE

Light Output (Lumens) **670**
Watts **11**
Lumens per Watt (Efficacy) **60.91**

Color Accuracy **90**
Color Rendering Index (CRI)

Light Color **3000 (Bright White)**
Correlated Color Temperature (CCT)

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-D5JFSJ (1/10/2017)
Model Number: 531861##(##=41-50)
Type: Retrofit Kit - Downlight



The Americas Headquarters
720 Corporate Woods Parkway
Vernon Hills, IL 60061
855-384-7754
www.etissl.com

