

# 8" Color Preference™ Downlight

53189111

Part # DL-8-40-902-MV-D

## SPECIFICATIONS




The ETi LED 8" Color Preference Downlight produces the kind of light power you want for brightness and precision in most commercial lighting applications. Ideal for retail environments when you need just the right color to accent an area, the color preference feature allows you to set the mood you want all the while reducing energy and maintenance cost when compared with conventional light sources. Designed to fit a 8" or 10" can, a 10" trim option is available to instantly convert it for a 10" can. Available in warm white, natural white and pure white.

ETi SSL offers an expansive line of energy efficient LED downlights. These fixtures are approved for most wiring and ceiling types. Typical applications include; indoor recessed can, high hat in residential, office, retail, restaurant, school, hospital, hotel, and motel locations.

### KEY FEATURES & BENEFITS

40Watt  
 3000lm  
 3000K/4000K/5000K  
 120-277V  
 CRI≥90  
 0-10V Dimmable  
 Wet Locations  
 50,000 rated life  
 5 Years Warranty  
 Operating Temperature: -4°F~113°F

### FIXTURE DIMENSIONS



Part # DL-8-40-902-MV-D  
 Dimension A=9.76"  
 Dimension B=4.74"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etissl.us/fcc15b](http://www.etissl.us/fcc15b)

# 8" Color Preference™ Downlight

53189111

Part # DL-8-40-902-MV-D

## SPECIFICATION DATA

Part #	Model Number	Description	Watts	Input Voltage (VAC)	Average Rated Life <sup>1</sup>	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CRI <sup>4</sup>	Power Factor	R9	Beam Angle	Operating Frequency
DL-8-40-902-MV-D	53189111	8"/10" color preference downlight	40	120-277	50,000 hours	3000	3000/4000/5000	≥90	>0.9	56	100	50/60Hz

<sup>1</sup> Hours lifetime with 70% lumen maintenance

<sup>2</sup> Thermally stable typical lumens

<sup>3</sup> in compliance with ANSI C78.377 2011

<sup>4</sup> Color rendering index/Ra

## SHIPPING INFORMATION


Item Number	Item UPC	Item Dimensions (L x W x H)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (L x W x H)	Inner Pack Weight (lbs) Dimensions (L x W x H)	Master Pack QTY	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
53189111	849489 006383	9.21"x4.74"	1.44	NA	NA	NA	NA	4	5084948 9006388	21.73"x11.57" x11.57"	10.49
90600193	NA	11.81"x7.87" x0.33"	0.40	NA	NA	NA	NA	20	5084948 9009945	12.36"x9.29" x12.91"	12.50

### 8" Downlight



+

### 10" Trim



=

### 10" Downlight



The Americas Headquarters  
 720 Corporate Woods Parkway  
 Vernon Hills, IL 60061  
 855-384-7754  
[www.etissl.com](http://www.etissl.com)

