

20" Reva Flushmount

LED

30 Watt 2200lm Round Flushmount Specifications



The ETi 20" LED Reva dimmable flushmount fixture offers exceptional performance for precision lighting applications, while reducing energy and maintenance costs when compared with conventional light sources. Using only 30 watts of power to deliver 2200 lumens and lasting more than 5-10 times longer, the Reva flushmount fixture is a high quality replacement for incandescent or fluorescent fixtures. Available in 4000K CCT and cULus listed for use in damp locations, the Reva flushmount fixture has a warranty of 5 years. Suitable for installations from -4° F to 95° F.


KEY FEATURES & BENEFITS

- 30 Watts - Low Power and High Performance
- 2200 lumens
- Dimmable
- 4000K CCT/82 CRI
- UL Rated for Damp Locations
- Replaces most applications using 200w incandescent lamps
- Rated life 50,000 hours (45.6 years)



This light source meets restrictions on hazardous substances.

FIXTURE DIMENSIONS



SKU# 54618244
Dimension A = 20"
Dimension B = 4.7"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a standard incandescent or fluorescent fixture is used. Typically used in bedrooms, hallways, kitchens, living rooms and recreational rooms. Other applications apply in commercial, office, retail, restaurants, schools, hospitals and hotel/motel locations.



855-384-7754 www.etissl.com

30 Watt 2200lm 20" Round Flushmount

LED

SPECIFICATION DATA

Project _____

Item Number _____

Prepared by _____ Date _____

ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
54618244	Dimmable Flushmount	30	120	50,000	2200	4000K	90	>.9	56	-0.0019	N/A	120	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens (±10%)													
³ Thermally stable CCT (±10%)													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
54618244	8494 8900 0244	20" x 20" x 4.66"	2.76	N/A	N/A	N/A	N/A	2	508494 8900 0249	23" x 22.5" x 11.8"	5.4



LED lighting facts[®]
A Program of the U.S. DOE

Light Output (Lumens) 2200
Watts 30
Lumens per Watt (Efficacy) 73.33

Color Accuracy
Color Rendering Index (CRI) 82

Light Color
Correlated Color Temperature (CCT) 4000 (Bright White)

Warm White 2700K 3000K Bright White 4000K Daylight 4500K 6000K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-00382V (5/19/2014)
Model Number: 54618244/CXK could be 41-50
Type Lumens: Other

ADA Compliant

Meets American with Disabilities Act standard extension requirements

ETi Solid State Lighting, Inc.
720 Corporate Woods Pkwy.
Vernon Hills, IL 60061

855-384-7754 www.etissl.com