



# 4' High Lumen Output Wrap Light

5200 lms | 120-277VAC | Model 54677441 | Part WR-4-57-940-MV-D

- > Energy Saving 57Watt Integrated LED
- > Uses 37.5% Less Energy than Equivalent 96 Watt T8 Fluorescent
- > Cool White 4000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

<b>Model</b>	54677441
<b>Part</b>	WR-4-57-940-MV-D
<b>Description</b>	4' High Lumen Output Wrap Light - 0-10V Dimmable (T24)
<b>Input Voltage (VAC)</b>	120-277
<b>Wattage</b>	57
<b>Dimmability</b>	0-10V
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	5200
<b>CCT<sup>3</sup></b>	4000k
<b>Location Rating</b>	UL Damp
<b>CRI<sup>4</sup></b>	≥90
<b>Beam Angle</b>	110°
<b>Operating Temperature</b>	Min -4°F (-20° C), Max 113°F (45° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	77
<b>DUV</b>	-0.00303
<b>CBCP</b>	1782
<b>Operating Frequency (Hz)</b>	50/60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754



ETI

**LED lighting facts**  
A Program of the U.S. DOE

<b>Light Output (Lumens)</b>	<b>5200</b>
<b>Watts</b>	<b>57</b>
<b>Lumens per Watt (Efficacy)</b>	<b>91.23</b>
<b>Color Accuracy</b>	
Color Rendering Index (CRI)	<b>90</b>
<b>Light Color</b>	
Correlated Color Temperature (CCT) <b>4000 (Bright White)</b>	
2700K	3000K
Bright White	Daylight
4500K	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: 5BAM-WHVNDV (Revised 6/28/2017)  
 Model Number: 546774XX(XX=41-50)  
 Type: Luminaire - Desk/Task



# 4' High Lumen Output Wrap Light

5200 lms | 120-277VAC | Model 54677441 | Part WR-4-57-940-MV-D

## SHIPPING INFORMATION

Model	54677441
Part	WR-4-57-940-MV-D
UPC	849489009995
Product Dimensions (L x W x H in.)	48 x 10 x 3.2
Product Dimensions (L x W x H cm.)	122 x 25.4 x 8.1
Product Weight (lbs.)	6.4
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489009990
Master Carton Dimensions (L x W x H in.)	50.39 x 10.39 x 12.52
Master Carton Dimensions (L x W x H cm.)	128 x 26.4 x 31.8
Master Carton Weight (lbs)	19.8
Pallet Quantity	40

## COMPATIBILITY

Sensors: 90600144, 90600145

Dimmer Brand	Dimmer Model#	Dimmer Brand	Dimmer Model#
Lutron	SCL-153PR-WH	Leviton	81000-I
Lutron	MACL-153M-WH	Leviton	IPL06
Lutron	MSCL-OP153M-WH	Leviton	IPL06-10Z
Lutron	DV-603PG-AL	Legrand	ADWR703HW4
Lutron	LG-600H-WH	Cooper	SCL03P-A-K
Lutron	GL-600H-DK	Cooper	DLC03P-LA
Lutron	TG-603PGH-WH	Aspire	9534DS-K
		Aspire	9573WS

## AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
90600144	NA	Step-dimming motion sensor	NA	120-277	4
90600145	NA	ON/OFF motion sensor	NA	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754

**ETi Solid State Lighting, Inc.**  
 720 Corporate Woods Parkway  
 Vernon Hills, IL 60061  
 Phone: 855.384.7754  
 Fax: 847.383.6256