



# 7" Spin Light™

830 lms | 120VAC | Model 54483141 | Part SL-7-11-840-SV-N

- > Energy Saving 11.5 Watt Integrated LED
- > Uses 81% Less Energy than Equivalent 60 Watt Incandescent Bulb
- > Cool White 4000k CCT
- > Lasts 45.6 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > US Patent # 9500352, 9541270, D776326
- > CND Patent # 169113



## SPECIFICATIONS

Model	54483141
Part	SL-7-11-840-SV-N
Description	7" Spin light- Non-Dimmable
Input Voltage (VAC)	120
Wattage	11.5
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	830
CCT <sup>3</sup>	4000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	23
DUV	0.00015
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)

ETI

**LED lighting facts**  
A Program of the U.S. DOE

Light Output (Lumens)	<b>830</b>
Watts	<b>11.5</b>
Lumens per Watt (Efficacy)	<b>72.17</b>
Color Accuracy	<b>80</b>
Color Rendering Index (CRI)	
Light Color	<b>4000 (Bright White)</b>
Correlated Color Temperature (CCT)	
Warm White	Bright White
2700K	3000K
	4500K
	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: 5BAM-FBICF4 (Revised 8/28/2017)  
 Model Number: 544831##(##=41-50)  
 Type: Luminaire - Decorative

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 7" Spin Light™

830 lms | 120VAC | Model 54483141 | Part SL-7-11-840-SV-N



## SHIPPING INFORMATION

Model	54483141
Part	SL-7-11-840-SV-N
UPC	849489002118
Product Dimensions (L x W x H in.)	7.01 x 7.01 x 3.54
Product Dimensions (L x W x H cm.)	17.8 x 17.8 x 9.0
Product Weight (lbs.)	0.73
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	5
Master Carton Bar Code	50849489002113
Master Carton Dimensions (L x W x H in.)	20.51 x 7.91 x 8.27
Master Carton Dimensions (L x W x H cm.)	52.1 x 20.1 x 21.0
Master Carton Weight (lbs)	5.83
Pallet Quantity	300

## AVAILABLE ACCESSORIES

Model	Description
95448314101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

ETi Solid State Lighting, Inc.  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256