



4' LED Vapor Tight

43 Watts 3600 Lumens



The ETi 4' Industrial LED Vapor Tight Fixture offers high quality, energy efficient performance in place of old, outdated HID and fluorescent light sources. Featuring durable construction, it is appropriate for industrial environments in either interior or exterior applications.

Rated for 50,000 hours and producing 3600 lumens of bright white light (4000K CCT), it is the perfect energy efficient, long life installation for parking garages, manufacturing environments, refrigerated cases, and cold storage facilities.

This multi-volt, Energy Star certified LED fixture has a high impact polycarbonate diffuser. Suitable for temperatures from -4° F (-20° C) to 95° F (20° C). cULus listed for use in wet locations. Warranty 5 years.

KEY FEATURES & BENEFITS

- 43 Watts — Low Power and High Performance
- 3600 lumens
- 120v—277v
- 4000k CCT, CRI 86
- cUL Rated for Wet Locations
- IP65 Rated
- Rated life 50,000 hours



This light source meets restrictions on hazardous substances.

FIXTURE DIMENSIONS



SKU# 54656142

Length = 47.7"

Width = 4.57"

Height = 2.91"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Industrial applications include manufacturing environments, warehouses, refrigerated and cold storage facilities, and parking garage bays and canopies.

855-384-7754 www.etissl.com

4' LED Vapor Tight

43 Watts, 3600 Lumens

SPECIFICATION DATA

Project _____
 Item Number _____
 Prepared by _____
 Date _____



ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
54656142	Industrial Vapor Tight	43	120-277	50,000	3600	4000K	86	>.9	21	-0.0006	N/A	115	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens (±10%)													
³ Thermally stable CCT (±10%)													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
54656142	8494 8900 9339	3.4" x 50" x 4.8"	5.07	N/A	N/A	N/A	N/A	2	508494 8900 9334	5.35" x 50.91" x 7.32"	11.57

LED lighting facts
 A Program of the U.S. DOE

Light Output (Lumens) 3600
 Watts 43
 Lumens per Watt (Efficacy) 83.72

Color Accuracy Color Rendering Index (CRI) 80

Light Color Color Temperature (CCT) 4000 (Bright White)

Warm White 2700K 3000K Bright White 4000K Daylight 5000K

All results are according to IESNA LM-79-2008, Approved Method for the Electrical and Photometric Testing of Solid State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 1164-8P/UE (3/4/2015)
 Model Number: S4656142 (before '14' denotes 41-00; color temperature standard 4000K)
 Type: Luminaire - Linear

ADA Compliant

Meets American with Disabilities Act standard extension requirements

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

ETi Solid State Lighting, Inc., 720 Corporate Woods Parkway, Vernon Hills, IL 60061

855-384-7754 www.etissl.com