

4' LED Wrap Light: Motion Sensor

LED

54676142

40 Watt 3600lm LED Motion Wrap Specifications




The ETi 4' LED Wrap Light with integrated motion and controller, offers exceptional performance as a high quality replacement for traditional fluorescent light sources. Using only 40 watts of power to deliver 3600 lumen and lasting more than 5 times longer than fluorescent alternatives, this wrap light reduces energy and maintenance costs while increasing rebate incentives for your next project. Stocked in Vernon Hill the cETLus listed fixture for use in damp locations, has a warranty of 5-years. Suitable for installations from -4° F to 95° F.

KEY FEATURES & BENEFITS

- 39.5W — 94.4lm/W
- 3600 lm
- 4000K CCT
- 90 CRI
- cETLus Rated for Damp Locations
- No IR or UV emission
- Rated life 50,000 hours



FIXTURE DIMENSIONS



SKU# 54676142
Dimension A = 48"
Dimension B = 3"



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a standard fluorescent fixture is used. Typically used in utility rooms, workshops, garages and recreational rooms. Other applications apply in commercial, office, retail, restaurants, schools, hospitals and hotel/motel locations.



4' LED Wrap Light: Motion Sensor

LED 54676142

ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	ϕ	Beam	Operating Frequency
54676142	LED Wrap w/ motion sensor and photo-controller	0	120	50,000	3600	4000K	0	>.9		-□	□	156	60Hz

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
54676142	8494 8900 0817	3" x 48" x 6"	4.11	N/A	N/A	□ □	□	□	508494 89000812	□x 52.68" x 8.66"	□

Sensor Specifications



LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) 3600
Watts 39.5
Lumens per Watt (Efficacy) 91.14

Color Accuracy 90
Color Rendering Index (CRI)



Light Color 4000 (Bright White)
Correlated Color Temperature (CCT)

Warm White 2700K Bright White 3000K Daylight 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-NM27K4 (Revised 1/27/2018)
Model Number: 546761XXX41-50
Type: Luminaire - Other



Operating voltage	120VAC 50/60Hz
Switched power	200W (Capacitive load)
Standby power	<0.5W
Detection area	10% / 50% / 75% / 100%
Hold time	5s / 90s / 5min / 15min
Daylight threshold	2lux / 1.0lux / 50lux, Disable
Microwave frequency	5.8 GHz +/- 75MHz
Microwave power	<0.2mW
Detection range	(Ø x H): 10m x 6m
Detection angle	30° ~ 150°
Mounting height	6m
Operating temperature	-20°C ~ 60°C
IP rating	IP20
Certificate	ETL, FCC

855-384-7754 www.etissl.com