

**NLOPAC-R4509 / NLOPAC-R6509**

AC Opal Series - Surface Mounted LED

Source: 10.5W or 15W LED  
 650lm or 1050lm

**PRODUCT DESCRIPTION**

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

**FEATURES:**

- 4" / 650lm / 10.5W
- 6" / 1050lm / 15W
- High color rendition: 90+ CRI
- AC LED (No Driver)
- Dimmable
- 2700K, 3000K, 4000K or 5000K
- White, bronze or natural metal finishes.
- Mount on standard 4" junction box.
- ENERGY STAR certified

**CONSTRUCTION**

**Housings:** One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

**Mounting:** AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon or round electrical junction boxes. Can be used with 4" (NLOPAC-R4) or 6" (NLOPAC-R6) fire-rated electrical junction boxes.

**Optics:** Nora specified and designed precision molded lens for optimal lumen output and even distribution.

**Finishes:** Available in white, bronze and natural metal finishes.

**Ratings:** IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

**ELECTRICAL**

**Input Voltage:** 120VAC

**Delivered Lumens / Wattage:**

**R4** = 650lm / 10.5W

**R6** = 1050lm / 15W

**Color Temperature:** 2700K, 3000K, 4000K, 5000K

**CRI:** 90+CRI


**Dimming:** 5% with ELV dimmer

10% with Triac dimmer

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

**ACCESSORIES**

**NLOPAC-56RECKIT:** 6" Opal can be mounted on 5" or 6" recessed housing using optional torsion spring kit.



**NLOPAC-4BKT-2:** Universal bracket for mounting 4" & 6" Opal to 3" or 4" junction boxes. Universal bracket is included with 4" Opal, must be specified for 6".



**LABELS AND LISTINGS**

- cULus Listed for Wet Location
- ENERGY STAR certified
- 5-Year Limited Warranty




**PRODUCT IMAGES AND DIMENSIONS**

**NLOPAC-R4509 4" AC Opal**




Shown in Natural Metal (N) finish



**NLOPAC-R6509 6" AC Opal**



Shown in White (W) finish



**AC Opal Series**

Size / Lumens / Wattage	Color Temperature	Finish
<b>NLOPAC-R4509</b> = 4" / 650lm / 10.5W	<b>27A</b> = 2700K	<b>BZ</b> = Bronze
<b>NLOPAC-R6509</b> = 6" / 1050lm / 15W	<b>30A</b> = 3000K	<b>N</b> = Natural Metal
	<b>40A</b> = 4000K	<b>W</b> = White
	<b>50A</b> = 5000K <sup>1</sup>	

<sup>1</sup> Available in white finish only

**Optional Accessories**

Description
<b>NLOPAC-56RECKIT</b> = 5"/6" Recessed Mounting Kit
<b>NLOPAC-4BKT-2</b> = Universal Bracket (included w/ 4")

Example: **NLOPAC-R650930AW** - 6" AC Opal LED, 1050lm / 15W, 3000K, White finish