
# **StarStrand® Aqua Star 24**

### **Features**

- Waterproof IP68 LED tape
- · Chemical and UV resistant plastic cover
- Long runs up to 50'
- · Installs into aluminum channel or silicone mouting clips
- · High lumen double chip LED
- · Multiple lengths with watertight IP68 connectors
- · Field cuttable every 4 inches
- \*See IP Chart on page 55

# **Applications**

- · Swimming pools and fountains
- · Outdoor decks
- · Step and stairs
- Landscape lighting
- · Outdoor building accent lighting











Item	Length	Diodes	Wattage	Lumens	Color Temp	CRI	PC Board	Beam	Voltage	Current
53441	24"	36	5.4	256	3500 K	70-75	Black	120°	24V	225mA
53442	60"	90	13.5	640	3500 K	70-75	Black	120°	24V	563mA
53443	120"	180	27	1280	3500 K	70-75	Black	120°	24V	1.1A
53445	300"	450	67.5	3200	3500 K	70-75	Black	120°	24V	2.8A

Model Number	Wattage	Maximum Run	Wiring Diagram
53380	60 Watts	21'	2
53316	100 Watts	30'	2
53381	150 Watts	50'	2

Wiring Diagram on page 60

3500 K 120°					
Distance		Foot Candles			
	12in	29.54			
	24in	8.42			
	36in	3.86			
	48in	2.2			

Shown using 1 foot section of Aqua Star 24



# StarStrand® Aqua Star 24

# 24V Outdoor Connecting Cords



**53364** 48"L x .75"W **53365** 144"L x .75"W

- Extend distance between 24V Weatherproof Driver and Aqua Star 24
- Extend distance between two sections of Aqua Star 24
- IP68 rated for underwater application up to 10'

#### **Aluminum Channel**



#### 53373

60"L x .75"W x .75"

- · Can be recessed or surface mount
- · Aluminum screws included

# 45° Angle Mounting Channel



#### 53374

48"L x 1"W x .75"

- Surface mount to angle tape for accent lighting
- Aluminum screws included

# Silicone End Cap Kit



#### 53368

.75"L x .5"W x .1"H

- · Placed on run termination
- Protects against water and damage

# **Mounting Clip**



#### 53370

.5"L x .5"W x .25"H

- Use to secure Aqua Star 24 to surface
- · Stainless steel screws included
- Clear polycarbonate plastic
- Package of 6

### **Drivers**

(See page 55 for detailed driver information)

53380 24V 60w Weatherproof Class II Driver

53316 24V 100w Weatherproof Class II Dimmable Driver

53381 24V 150w Weatherproof Class II Driver