

# StarStrand® Controllers



## 24V RGB Controller

### 53385

6"L x 2.5"W x 1"H

- Controls color, color intensity and speed
- Controls 30' of Rainbow Star 24 or Rainbow Channel Star 24
- RF remote control included
- 4" 6-Pin input cord, 72" 4-Pin output cord

### Remote Functionality

Six button RF remote controls include on/off, brightness up/down, speed up/down, mode choice

### Modes - 10

Static red, static yellow, static green, static cyan, static blue, static purple, static white, single color rotate, red-green-blue single color jump, colors gradually change in circles



## 24V Weatherproof RGB Controller

### 53389

5"L x 2.5"W x 1"H

- Controls color, color intensity and speed
- Controls 30' of Rainbow Aqua 24
- RF remote control included
- IP65 rated (not submersible)

### Remote Functionality

Four button RF remote controls include on/off, speed up/down, mode choice

### Modes - 9

Static red, static yellow, static green, static cyan, static blue, static purple, static white, single color jump, colors gradually change



## 24V Dimming Controller

### 53393

5"L x 2.5"W x 1"H

- Full range dimming
- Controls up to max run of Ultima Star 24, Solar Star 24, Elite Star 24 and Channel Star 24
- RF remote control included
- All 24V Dimming Controllers are on the same RF frequency
- Compatible with drivers 53313, & 53318

### Remote Functionality

Six button RF remote controls include on/off, brightness up/down

## 24V DMX512 Interface/Decoder & Standalone RGB Controller



### 53387

7.5"L x 4.5"W x 1.5"H

- Meets DMX512 protocol and can be used as DMX interface/decoder
- As a standalone controller, it can control color, color intensity and speed
- Controls 30' of Rainbow Star 24 or Rainbow Channel Star 24
- RF remote control included
- 4" 6-Pin input cord, 72" 4-Pin output cord, and 12" XLR3 connecting cord
- XLR3 male and female interface to connect multiple units together

### Modes - 33

Static red, static green, static blue, static yellow, static purple, static cyan, static white, 7-color jump, 6-color jump, 7-color flick, red/green jump, red/blue jump, green/blue jump, red/green/blue jump, red/green flick, red/blue flick, green/blue flick, red/green/blue flick, red/green/blue smooth, red/green smooth, red/blue smooth, green/blue smooth, red/green/blue gradual, red/green gradual, red/blue gradual, green/blue gradual, red gradual, green gradual, blue gradual, red dim mode, green dim mode, blue dim mode, red/green/blue mix

### Remote Functionality

Four button RF remote controls include mode choice, mode set, up and down

## Rainbow Dial Controller



### 53600

9"W x 1.8"H

- 16 color patterns
- Dimmable while on static colors
- Pause functions while doing skipping or gradual changes
- 50 levels for brightness adjustment
- 50 levels for speed adjustment
- Remote is powered with a rechargeable battery
- Charger and holder are included
- Additional Rainbow Dial RGB Controller available 53601

### Remote Functionality

Multi-Function remote where the color id displayed in the center of the dial, allowing the user to not have to be located in the view of the tape.

### Modes - 16

Static red, static green, static blue, static yellow, static purple, static cyan, static white, colors quickly change, red fades, green fades, blue fades, yellow fades, purple fades, cyan fades, white fades, colors gradually change

## 24V Color Flex Controller



### 53398

4"W x 4"L x 2"H

- Controls up to 20' of Color Flex Star 24 using RF remote control or wall controller, both which are included
- Adjusts color temperature from 2900 K to 5500 K
- 4" 6-Pin power input cord, 72" 4-Pin signal output cord

### Remote Functionality

Eight button RF remote controls included on/off, color temperature selection, speed up/down, brightness up/down and pause capability

# StarStrand® Controllers



## Digital Rainbow Star WiFi Controller

**53392**

2.95"W x 1"H x 4"L

- Uses iPad® / iPhone® / iPod touch® to control system when both device and controller are on the same network
- Download free app from iTunes
- IOS user interface for easy operation
- 347 preset chasing modes
- 50 user defined custom modes



## Digital Rainbow Star DMX Interface/Controller

**53388**

4.5"W x 1.5"H x 7.5"L

- Controls up to four 300 foot sections of StarStrand Digital Rainbow Star
- Four channels of simultaneous output
- 36 modes and patterns
- One DMX512 (1990) protocol mode
- 32 grayscale levels
- 60 levels of speed adjustment
- Power off data memory
- LCD screen shows working status



## Digital Rainbow Star Controller

**53391**

2.5"W x 1"H x 4"L

- Controls up to 300 feet of StarStrand Digital Rainbow Star
- 36 modes and patterns
- 20 levels of speed adjustment
- 16 levels of brightness
- Power off data memory
- Remote control included