



Features

- 14AWG SJTW (2-wire LS & LS2, 3-wire ETLS cable with medium and suspended medium base (E26)
- Formulated PVC sockets form a tight seal around bulbs to preclude the entrance of water and moisture
- Suspended socket has T-mold with mounting hole; Non-suspended socket has two mounting ears built into the base
- Use Commercial Grade Light String with Long Life Incandescent Lamps (page 199) or Pro Decorative lamps (pages 190-197); lamps sold separately

Available Colors



Black



Green



White

Listing / Ratings



ROHS COMPLIANT

E26 Commercial Grade Light String

Use Commercial Grade Light String in reels, interconnect-able kits, or cord and plug sets with three socket size and spacing combinations for decorative/event/festive lighting applications. Suitable for outdoor, year-round use. For spans up to 20 feet, use eye bolts and plastic ties to anchor ends. For spans longer than 20 feet, use catenary cable (sold separately) with plastic ties at each socket.


Technical Information

Series	LS / LS2 / ETLS
Input Voltage	120V AC, 60Hz
Wattage	Max per socket: 25W (LS & LS2) / 40W (ETLS)
Max Run	See individual product
Socket	E26 (medium)
Spacing	24" (E26)
Cuttable	Yes*
IP Rating	IP64**
Rating	Suitable for outdoor, year-round use*
Rated Life	Varies by lamp used


*All LS products are non-rated; LS2 and ETLS interconnect-able kits are cETLus Listed for wet location use, however safety rating is void if product is cut


**For non-cut cETLus Listed LS2 product, interconnected strings must be properly sealed and strain relief protected with electrical tape at each connection point. For non-rated LS product, any cut ends must be sealed with LS-M/MS-END and/or electrical tape (ensure proper seal to preclude entrance of water).

Medium (E26) Base • cETLus Listed




Medium (E26) Base
48ft Interconnectable Sets
 24 sockets / 24" socket spacing
 25W max per socket / cETLus Listed up to 1200W max
 14AWG SJTW 2-wire / 120V plug and socket
 2-wire interconnectable male/female ends
LS2-M-24-48-BK (Black)





Suspended Medium (E26) Base
48ft Interconnectable Sets
 24 sockets / 24" socket spacing
 40W max per socket / cETLus Listed up to 1440W max
 14AWG SJTW 3-wire / 120V plug and socket
 3-wire interconnectable male/female ends
ETLS-MS-24-48-BK (Black)



Medium (E26) Base • Non-Rated



Medium (E26) Base
48ft 'Cord and Plug' Sets
 24 sockets / 24" socket spacing
 25W max per socket / 600W max per string
 14AWG SJTW 2-wire / 120V plug w/terminated end
LS-M-24-48-GR (Green)



Medium (E26) Base
100ft 'Cord and Plug' Sets
 50 sockets / 24" socket spacing
 25W max per socket / 1250W max per string
 14AWG SJTW 2-wire / 120V plug w/terminated end
LS-M-24-100-BK (Black)



Medium (E26) Base
330ft Bulk Reels
 165 sockets / 24" socket spacing
 25W max per socket / 1800W max per string
 14AWG SJTW 2-wire / No plug or terminated end
LS-M-24-BK (Black)
LS-M-24-GR (Green)

Suspended Medium (E26) Base • Non-Rated



Suspended Medium (E26) Base
48ft 'Cord and Plug' Sets
 24 sockets / 24" socket spacing
 25W max per socket / 600W max per string
 14AWG SJTW 2-wire / 120V plug w/terminated end
LS-MS-24-48-BK (Black)
LS-MS-24-48-GR (Green)



Suspended Medium (E26) Base
100ft 'Cord and Plug' Sets
 50 sockets / 24" socket spacing
 25W max per socket / 1250W max per string
 14AWG SJTW 2-wire / 120V plug w/terminated end
LS-MS-24-100-BK (Black)
LS-MS-24-100-WH (White)



Suspended Medium (E26) Base
330ft Bulk Reels
 165 sockets / 24" socket spacing
 25W max per socket / 1800W max per string
 14AWG SJTW 2-wire / No plug or terminated end
LS-MS-24-BK (Black)
LS-MS-24-GR (Green)
LS-MS-24-WH (White)

Accessories



CGLS End Caps
 Black plastic end cap for 14AWG SJTW
 Commercial Grade Light String
LS-M/MS-END (Black)