

LED PANORAMA EXTENSION ARMS

Installation instructions for AL-4C-DB and AL-4C-WH

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THESE ACCESSORIES. FAILURE TO FOLLOW INSTALLATION INSTRUCTIONS AND ALL APPLICABLE ELECTRICAL CODES WILL VOID THE PRODUCT WARRANTY.

WARNING:

These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes and/or the current National Electric Code (NEC).

WARNING:

Disconnect supply power from the source prior to installation. This product and its accessories must be installed by a person familiar with the construction and operation of the product and the hazards involved, and in accordance with current electrical codes and/or the current National Electric Code (NEC). Consult a local licensed electrician if you are not sure about the installation. To reduce potential of electric shock, fixture must be grounded.

APPLICATION / USE:

This accessory extension arm is designed for use with American Lighting's Panorama Flood Lights in surface mount applications only. See fixture instructions in addition to these instructions

INSTALLATION:

Disconnect supply power from the source prior to installation.

1. For AL-1H and AL-2H versions, start by loosening the locknut on the canopy to remove it. With canopy off, feed the black, white and copper wires through the 1/2" opening of the extension arm, thread the fixture's mounting arm into the extension and secure it with the 1/2" locknut.
2. Continue installation by following fixture's instruction sheet.



AMERICAN LIGHTING
BRIGHT IDEAS • INNOVATIVE PRODUCTS