# WARM WHITE WALL WASHERS

Three fixture lengths of sealed aluminum housings create this durable family of high impact illumination, for use indoors or outdoors.

### Performance

- 3300K Warm White LED light with 80 CRI washes surfaces with energy efficient light that looks like halogen
- LED Wall Washers have a 25° beam angle and emit up to 2600 lumens
- Long life high power LEDs last up to 60,000 hours, reducing maintenance costs


#### Construction

- Durable aluminum alloy housing with enamel finish
- Housing and base with built-in driver are fully sealed for use in wet locations (IP65)
- Well designed thermal management keeps LEDs cool, maximizing longevity

#### Installation

- Easy to install each unit has its own five foot grounded power cord
- Integrated mounting holes in base/leg brackets and adjustable tilt design maximize on-site flexibility
- Use GFCI weatherproof outlet for outdoor installations

# Photometrics (LLW48-WW)



\*Footcandle values based on 10ft mounting height.

# Specifications

LLW WW Series
120V, 60Hz AC
3300K
80+
16W / 32W / 48W
850LM / 1700Lm / 2600Lm
N/A
25°
Die-cast aluminum alloy
Tempered glass
N/A
See individual product
Wall or ground via brackets
N/A
24 or 36 x BridgeLUX LEDs
60,000 hrs

#### LED Linear Wall Washer



## LLW16-WW

LED Linear - 16W 3300K / 850Lm 15.75"L x 2-3/16"W x 5"H



## LLW32-WW

LED Linear - 32W 3300K / 1700Lm 31.5"L x 2-3/16"W x 5"H



# LLW48-WW

LED Linear - 48W 3300K / 2600Lm 47.25"L x 2-3/16"W x 5"H

## Building a System

For WW, select sizes and quantities and plan to provide an outlet location (GFCI for outdoor fixtures) within five feet of each fixture.