

STARSTRAND® 12V Drivers



12V 30w Class II Driver

53302

5.7"L x 1.9"W x 1.2"H

- Electronic direct wire driver
- 120V-264V input
- 12V, 2.5A output
- Short circuit protection, overload protection, over voltage protection
- Constant current
- Operating temperature: -4°F to 140°F
- IP64 rated
- Includes 72" 4-Pin output cord
- Class II UL1310, UL-RU certified



12V 40w Class II Driver

53329

4"W x 1.5"H x 5.75"L

- Required every 16'
- Electronic direct wire driver
- 120V-277V input
- 12V, 3.3A output
- Short circuit protection
- Constant voltage
- IP67 rated
- Includes wiring compartment
- Includes 72" 4-Pin output cord
- Includes one power feed (53566)

STARSTRAND® Electronic Dimmable Drivers

Exclusive to StarStrand



40 - 100W Dimmable Driver

53330 110V Input

53331 277V Input

9"L x 1.8"W x 1.25"H

- Output Voltage DC24V 4A (100% Load) RMS
- Class 2 constant voltage
- Active PFC function
- Short circuit protection
- Efficiency > 85%
- OVC < 35V
- Minimum load 5 Watt
- Minimum dimmable load 30 Watt
- Wiring compartment w/ 3 x 1/2" KO
- Includes 6-Pin output cord
- Dimmable w/ standard triac dimmer



30W Driver

53324 Non Dimmable 110V - 277V

53326 Dimmable 110V

9.5"L x 2"W x 1.25"H

- Output voltage DC24V 1.25A
- Class 2 constant voltage
- PFC > .95
- Short circuit protection
- Efficiency > 85%
- OVC < 35V
- Minimum load 3 Watt
- Minimum dimmable load 5 Watt
- Wiring compartment w/ 3 x 1/2" KO
- Includes 6-Pin output cord
- Dimmable w/ standard triac dimmer